

**POLYURETHANE-BASE EMULSION COATING MATERIAL COMPOSITION**

**Patent number:** JP57070160  
**Publication date:** 1982-04-30  
**Inventor:** GOMI TADASHI; KAWAKAMI YASOTA; SHIMADA SHIGERU; KURODA AKIRA  
**Applicant:** YUUHOU SHIYOUKAI KK;; HODOGAYA CHEMICAL CO LTD  
**Classification:**  
- **International:** C08K5/06; C08L75/04; C09D3/72  
- **European:**  
**Application number:** JP19800146812 19801022  
**Priority number(s):** JP19800146812 19801022

**Abstract of JP57070160**

**PURPOSE:**A coating composition having the lowest coat-formable temp. lowered and capable of forming a coat at a normal to low temp. without deterioration of coat performance, which is prep. by compounding a polyurethane-base emulsion with a specified oxyalkylene glycol deriv.

**CONSTITUTION:**100pts.wt., based on the solid, polyurethane-base emulsion is compounded with 1-70pts.wt. oxyalkylene glycol deriv. of the formula (wherein A and A' are each a 1-5C hydrocarbon group, a 1-4C acyl group or H, which may be the same or different from each other; R is 2-4C alkylene; n is 1-3), to obtain the titled composition. **EFFECT:**A coat with excellent durability such as wear, water and detergent resistance, and adhesion is formed. **USE:**An all-purpose coating material usable for all materials such as a plastic for outdoor and indoor floors, a wall, outer wall, etc., wood, stone, ceramics or concrete.

---

Data supplied from the **esp@cenet** database - Worldwide